

LM-15

LENSMETER MODEL: LM - 1 5



**Lightweight, cordless models can be carried any place.
No cord to obstruct handling the lens meter
Also, now you can use our LM-15 with an AC adapter!**

Features


- New refined appearance with convenience-oriented design ensures operational ease.
- Troublesome lamp replacement is eliminated by an LED light source.
- The auto power-off function maximizes battery life even when the OFF-switch is forgotten. The batteries run for more than 200 hours continuously, and the power-off time is adjustable (2-6 min.).
- Can be clamped at any angle within from 45°~90° allowing measurement while in a comfortable position.
- Can be tilted to a full 90° for easy measurement of contact lenses.
- When an AC adapter is connected, the battery supply circuit is automatically closed to save battery life.

Specifications

Vertex refracting power	Measurement range	0~±25D
	Graduation	Within ±3D : 0.125D step Over ±3D : 0.25D step
Prism refracting power	Measurement range	0~5△D
	Graduation	1△D step
	With prism compensator	Max. 20 △D
Axis angle	Measurement range	0~180°
	Graduation (Internal)	1°
	Graduation (External)	5°
Inspection lens diameter	Measurement range	24~90 mm φ (Contact lens possible)
Tilting		45~90°
Power supply		SUM3 battery×2 or AC adapter (option)
Light source		LED
Dimensions		355(H)×340(D)×170(W)
Weight		3.6kg
Standard accessories		1 Dust cover 1 Standard lens holder 1 Contact lens holder 1 Bifocal lens holder
Optional accessories		Prism compensator Diopter range : 15 diopters Graduations : 1 diopter step Angle scale : 0~180° Graduations : 5° AC adapter (see specifications)



LM-15 (Internal reading type)



AC adapter (Specifications)

Out put : DC 3V 500mA
Out put plug size
Outside diameter : 5.5mm
Inside diameter : 2.5mm
Length : 9.5mm
Polarity : see below



Design and specifications are subject to change without notice.

Distributed by